

# LED BASED SINGLE OBSTRUCTION LIGHT

OL1B-LED120



## FEATURES

- Highly resistant glass construction
- Reduced energy consumption by 96% versus incandescent
- 10 year durability
- Very stable light output under voltage variations

## SPECIFICATIONS

### Light output

Lamp type	LED
Effective candelas	32.5 min.
Horizontal coverage	360°
Vertical beam	>10°
Expected min. lamp life	10 years

### Electrical value

	Models available in 120 or 240 Vac or 12/48 VDC
Power consumption	4 Watts
Current at 120Vac	0.06 A (rms)
Power requirements	120 or 240 Vac 50/60hz 12/48 VDC

### Mechanical

Weight	1.5 Kg (3.5 lbs)
Dimensions (W x H x D)	150mm x 150mm x 200 mm (5¾" x 5¾" x 7¾")
Hub sizes	¾" or 1" NPT
Lenses material	Pyrex glass
Base material	Aluminum

### Others

FAA type	L-810
Transport Canada type	CL-810
Operating temperature	-55°C to 55°C (-67°F to 131°F)
Warranty	5 years

### ETL CERTIFIED FOR FAA:

- AC 150/5345-43G

### COMPLIANT WITH:

-  Transports Canada     Transport Canada    Standard 621